



HOSHIZAKI ICE MAKER

IM series Ice production 65kg/day to 240kg/day

IM series Self-contained type




Cube Ice

Air Cooled Model

IM-65LE



Back side



Air Flow : Front in /
Right side out • Back side out

IM-65LE-25



IM-100LE



IM-240ME




Water Cooled Model

IM-65WLE



Back side



Air Flow : Right side in / Back side out

IM-65WLE-25



IM series Stack on type




Cube Ice

IM-240DME w/P-200SD2




Bottom



Air Flow : Front in • Right side in / Back side out

Left side



	Self-contained type						Stack on type
	IM-65LE	IM-65LE-25	IM-65WLE	IM-65WLE-25	IM-100LE	IM-240ME	IM-240DME
A (mm)	67	67	67	67	72	92	62.5
B (mm)	74	74	74	74	99	95	81
C (mm)	138	138	138	138	207	207	208
D (mm)	41	41	41	41	83	49	46
E (mm)	—	—	175	175	—	—	—
F (mm)	—	—	105	105	—	—	—
G (mm)	—	—	95	95	—	—	—

IM
Cube Ice
Self-contained type



IM-100LE

Cube size



L (Large)
28×28×32mm



M (Medium)
25×25×23mm

		IM-65LE	IM-65LE-25	IM-65WLE	IM-65WLE-25	IM-100LE	IM-240ME
Ice Production(kg/day)	Cube size	L	M	L	M	L	L
	A.T.21C/ W.T.15C	52	47	56	57	85	210
	A.T.32C/ W.T.21C	43	40	52	52	75	200
Bin Capacity (kg)		26	26	26	26	50	110
Cooling System		Air	Air	Water	Water	Air	Air
Refrigerant		R134a	R134a	R134a	R134a	R134a	R404A
Electrical Supply		1/230 60Hz	1/230 60Hz	1/230 60Hz	1/230 60Hz	1/230 60Hz	1/230 60Hz
Electrical Consumption (W/h)		470	470	430	430	700	1600
Water Consumption (M3/day)		0.20	0.27	0.24	0.3	0.25	0.50
Water Supply Inlet		G3/4	G3/4	G3/4	G3/4	G3/4	G3/4
Drain Outlet		R3/4	R3/4	R3/4	R3/4	R3/4	R3/4
Cooling Water Inlet		—	—	Rc1/2	Rc1/2	—	—
Cooling Water Outlet		—	—	Rc1/2	Rc1/2	—	—
Dimensions (mm)		W633 x D506 x H850	W633 x D506 x H850	W633 x D506 x H850	W633 x D506 x H850	W704 x D506 x H1200	W704 x D670 x H1577
Weight (kg) Net/Gross		63/69	63/69	59/65	59/65	80/90	130/145

IM
Cube Ice
Stack on type



IM-240DME
W/P-200SD2

Cube size



L (Large)
28×28×32mm



ML (Medium Large)
28×28×23mm



S (Small)
21×21×14mm

		IM-240DME
Ice Production (kg/day)	Cube size	L,ML,S
	A.T.21C/ W.T.15C	210
	A.T.32C/ W.T.21C	200
Bin Capacity (kg)		N/A
Cooling System		Air
Refrigerant		R404A
Electrical Supply		1/230 60Hz
Electrical Consumption (W/h)		1600
Water Consumption (M3/day)		0.50
Water Inlet		G3/4
Water Outlet		R3/4
Dimensions (mm)		W1084 x D800 x H395
Weight (kg) Net/Gross		90/95