



# HOSHIZAKI ICE MAKER

KM series / DCM series / DIM series

## KM series




Crescent Ice

KM-500MAH W/B-300bin



Back side



KM-150BAF



Air Flow : Front in / Front out

KM-280MAH  
W/B-300bin



KM-630MAH  
W/B-700bin



KM-900MAH  
W/B-900bin



KM-1300SAH  
W/B-900bin



## DCM series

Cubelet Ice and Water Dispenser




Cubelet Ice

DCM-60F



Top




Air Flow : Bottom in / Top out

DCM-110F



Top



Air Flow : Bottom in / Top out

## DIM series

Cube Ice Dispenser




Cube Ice

DIM-30AE



Back side



Air Flow : Front in / Back side out

	KM-150BAF	KM-280MAH	KM-500MAH	KM-630MAH	KM-900MAH	KM-1300SAH	DIM-30AE
A (mm)	520	294	294	294	286	794	60
B (mm)	91	37	37	67	58	52	85
C (mm)	w/olegs 46	25	25	25	25	23	320
D (mm)	317	128	128	128	126	195	175



KM-500MAH  
WB-300bin

	KM-150BAF	KM-280MAH	KM-500MAH	KM-630MAH	KM-900MAH	KM-1300SAH
Ice Production (kg/day)						
Type of ice	Crescent	Crescent	Crescent	Crescent	Crescent	Crescent
A.T.21C/ W.T.10C	71	121	226	272	380	582
A.T.32C/ W.T.21C	49	85	178	213	327	512
Bin Capacity (kg)	32	N/A	N/A	N/A	N/A	N/A
Cooling System	Air	Air	Air	Air	Air	Air
Refrigerant	R404a	R404a	R404a	R404a	R404a	R404a
Electrical Supply	1/115 60Hz	1/115 60Hz	1/115 60Hz	1/208 -230 60Hz	1/208 -230 60Hz	1/208 -230 60Hz
Electrical Consumption (W/h)@32C/21C	613	940	1212	1332	1965	2235
Water Consumption (M3/day)	0.16	0.19	0.43	0.60	0.93	1.30
Water Supply Inlet	3/8" (15.9mm) Flare	1/2" FPT	1/2" FPT	1/2" FPT	1/2" FPT	1/2" FPT
Drain Outlet	3/4" (19mm) FPT	3/4" FPT 3/8"OD Pipe	3/4" FPT 3/8"OD Pipe	3/4" FPT 3/8"OD Pipe	3/4" FPT 3/8"OD Pipe	3/4" FPT 3/8"ID Pipe
Dimensions (mm)	W635 x D711 x H994 w/legs	W560 x D695 x H770	W560 x D695 x H770	W560 x D695 x H950	W762 x D695 x H950	W1219 x D695 x H695
Weight (kg) Net/Gross	77/93	69/80	69/80	70/84	98/128	125/143




DCM-110F



DIM-30AE

Cube size



L (Large)  
28x28x32mm

	DCM-60F	DCM-110F	DIM-30AE
Ice Production (kg/day)			
Cube size	Cubelet	Cubelet	L
A.T.21C/ W.T.15C	60 ※1	110	33
A.T.32C/ W.T.21C	47 ※2	90	28
Bin Capacity (kg)	1.9	4	15
Cooling System	Air	Air	Air
Refrigerant	R134a	R134a	R134a
Electrical Supply	1/100 60Hz	1/100 60Hz	1/100 60Hz
Electrical Consumption (W/h)	340	480	335
Water Consumption (M3/day)	0.047 ※2	0.09	0.12
Water Supply Inlet	Rc 1/2"	Rc 1/2"	Rc 1/2"
Drain Outlet	Rc 3/4"	Rc 3/4"	Rc 3/4"
Dimensions (mm)	W350 x D480 x H720	W350 x D585 x H840	W350 x D500 x H1600
Weight (kg) Net/Gross	42/48	60/67	65/71

※1 A.T.20C/W.T.15C ※2 A.T.30C/W.T.25C

**HOSHIZAKI**